



August 29, 2019

Tracking Number: 374105

Authorization Number: 263

REGISTERED MAIL

Glencore Canada Corporation
Suite 718
22 - 2475 Dobbin Road
West Kelowna, BC V4T 2E9

Dear Permittee:

Enclosed is Amended Permit 263 issued under the provisions of the *Environmental Management Act*. Your attention is respectfully directed to the terms and conditions outlined in the permit. An annual fee will be determined according to the Permit Fees Regulation.

This permit does not authorize entry upon, crossing over, or use for any purpose of private or Crown lands or works, unless and except as authorized by the owner of such lands or works. The responsibility for obtaining such authority rests with the permittee. This permit is issued pursuant to the provisions of the *Environmental Management Act* to ensure compliance with Section 120(3) of that statute, which makes it an offence to discharge waste, from a prescribed industry or activity, without proper authorization. It is also the responsibility of the permittee to ensure that all activities conducted under this authorization are carried out with regard to the rights of third parties, and comply with other applicable legislation that may be in force.

This decision may be appealed to the Environmental Appeal Board in accordance with Part 8 of the *Environmental Management Act*. An appeal must be delivered within 30 days from the date that notice of this decision is given. For further information, please contact the Environmental Appeal Board at (250) 387-3464.

Administration of this permit will be carried out by staff from the Environmental Protection Division's Regional Operations Branch. Plans, data and reports pertinent to the permit are to be submitted by email or electronic transfer to the Director, designated Officer, or as further instructed.

Yours truly,



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

Enclosure

cc: BC Ministry of Energy, Mines and Petroleum Resources, Kamloops
Corporation of the District of Peachland, Attn: Joe Mitchell, Director of Operations
Interior Health, Attn: Gordon Moseley, C.P.H.I (C) 1440 - 14 Ave. Vernon, B.C.
V1B 2T1



**MINISTRY OF
ENVIRONMENT**

PERMIT

263

Under the Provisions of the *Environmental Management Act*

GLENCORE CANADA CORPORATION

**Suite 718
22 - 2475 Dobbin Road
West Kelowna BC V4T 2E9**

is authorized to discharge effluent to MacDonald Creek, tributary to Trepanier Creek, from a closed mining operation located near Peachland, British Columbia, subject to the terms and conditions listed below. Contravention of any of these conditions is a violation of the *Environmental Management Act* and may lead to prosecution.

This Permit supersedes and amends all previous versions of Permit 263 issued under Part 2, Section 14 of the *Environmental Management Act*.

1. AUTHORIZED DISCHARGES

Authorized Source

1.1. This section applies to the discharge of effluent from a WASTEWATER TREATMENT PLANT. The site reference number for this discharge is E226070.

1.1.1. The average rate of discharge is 3,100,000 cubic metres per year (January 1 to December 31).

1.1.2. The maximum rate of discharge is 6,000,000 cubic metres per year (January 1 to December 31).

1.1.3. The characteristics of the discharge must be equivalent to or better than:
Dissolved Copper:

Maximum: 0.03 mg/L

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)

Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

Total Iron:

Maximum: 0.50 mg/L

Annual Average: 0.35 mg/L (January 1 to December 31)

Dissolved Manganese:

Maximum: 0.25 mg/L, and subject to Sections 2.1 and 2.11

Dissolved Molybdenum:

Maximum: 0.25 mg/L and subject to Section 2.1

Dissolved Zinc:

Maximum: 0.2 mg/L

Total dissolved solids:

Maximum: 850 mg/L

pH Maximum: 8.5 pH units Minimum: 6.5 pH units

Dissolved Sodium :

Maximum: 100 mg/L

Dissolved Sulphate:

Maximum: 500 mg/L, and subject to Section 2.1

Total Suspended Solids:

Maximum: 15 mg/L

- 1.1.4 The authorized works are a wastewater treatment plant (including a polishing pond), tailings pond, open pit, seepage collection works, sludge management facility and related appurtenances approximately located as shown on Site Plan A.
- 1.1.5 The location of the facilities from which the discharge originates is DL 5159, Osoyoos Division Yale District and comprising mineral leases 319, 320, 323, 324, 325, 326 and 327.
- 1.1.6 The location of the point of discharge is the new channel of MacDonald Creek, downstream of the polishing pond, DL 5159, latitude N 49 52' 06", longitude W 119 55' 58", approximately as shown on the attached Site Plan A.

2. GENERAL REQUIREMENTS

2.1 Water Quality Objectives

The permittee must ensure that the following water quality objectives are maintained as a result of the discharge, in the entire reach of Trepanier Creek

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

below the discharge, as measured at the District of Peachland intake works:

Molybdenum:

Maximum monthly concentration: less than or equal to 0.03 mg/L
in any single sample,
from June 1 to September 30: less than or equal to 0.03 mg/L
from October 1 to May 31: less than or equal to 0.06 mg/L

Dissolved Manganese:

In any single sample, less than or equal to 0.05 mg/L.

Sulphate:

less than or equal to 100 mg/L annual average (January 1 to December 31).
less than or equal to 250 mg/L in any single sample.

Toxicity:

The discharge shall be non-toxic to freshwater aquatic species, as measured using a standard LC50 trout bioassay. Sampling will be conducted when required by the Director.

Definitions of Terms Used Within Section 2.1:

“Monthly concentration” means the arithmetic mean of concentration values within a calendar month, including background levels.

2.2 **Maintenance of Works and Emergency Procedures**

The Permittee must inspect the authorized works regularly and maintain them in good working order. In the event of an emergency or condition beyond the control of the Permittee, which prevents continuing operation of the approved method of pollution prevention, the Permittee must immediately notify the Director and take appropriate remedial action.

2.3 **Process Modifications**

The Permittee must notify the Director prior to implementing changes to any process that may affect the quality and/or quantity of the discharge.

2.4 **Unauthorized Discharges and Spill Reporting**

Effluent spills or spills of hazardous contaminants must be reported to the

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

Provincial Emergency Program Duty Officer immediately after occurrence, in accordance with the Spill Reporting Regulations, by calling the following toll-free telephone number:

1 (800) 663-3456

2.5 Seepage Collection and Return Works

The permittee must utilize seepage collection works located downstream of the main tailings dam, the saddle dam and the sludge management facility, and return recovered seepage to the tailings impoundment, the pit, or the water treatment plant.

2.6 Surface Diversion Works

The permittee must maintain diversion works to minimize the impact on the quality of surface water from mining activities by directing runoff from waste rock dumps and other disturbed areas to the tailings impoundment or to the pit or to the water treatment plant, and by diverting upstream waters around disturbed areas. The permittee must make application to the Regional Water Manager for approval of the installation of any surface diversion works.

The permittee may make application to the Director and the Regional Water Manager to return diverted waters to pre-disturbance surface watercourses following reclamation and re-vegetation activities. As part of that evaluation, the permittee may be required to provide appropriate monitoring results in order to demonstrate that the water quality objectives of the downstream waters will not be compromised.

2.7 Bypasses

The Permit Holder must not allow any discharge authorized by this authorization to bypass the authorized works, except with the prior written approval of the Director.

2.8 Provision of Alternate Water Supplies

If, at any time, there is insufficient flow in Trepanier Creek to provide the dilution necessary for the permittee to attain the required water quality objectives referred to in Section 2.1, the permittee may, at the permittee's discretion, cease to discharge, reduce the discharge to a sufficient level to attain the appropriate water quality objectives, or in exceptional

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

circumstances, continue to discharge while providing alternate water supplies for the licensed users of Trepanier Creek. The quality of any alternate water supplied must be equal to or better than the water quality objectives required under this Permit for the uses for which that water is licensed.

The permittee must contact the Regional Water Manager on a frequency of not less than once per year and request a current list of licensed water users. Information obtained from a government web site will suffice, if available and current.

2.9 **Prevention of Habitat Loss During Spring Freshet**

The permittee must cease to discharge during any period that the flow in Trepanier Creek exceeds ninety-nine per cent of the maximum instantaneous recorded flow, in order to minimize the loss of gravel and incubating eggs through stream scouring.

2.10 **Sludge Management Plan**

The permittee has characterized the quantity and quality of the sludge produced by the water treatment process, and submitted the following reports in support of a sludge management plan:

- “Sludge Disposal – Study of Options and Feasibility Design, Brenda Mine, British Columbia”, prepared by AMEC Earth & Environmental Limited, dated January 26, 2001;
- “Design Optimization for Phase 1 Sludge Disposal Facility, Brenda Mines, West Bank (sic), British Columbia”, June 2001, prepared by AMEC Earth & Environmental Limited
- Phase 1 Sludge Disposal Facility – Material Permeabilities/Dam Toe Drain”, September 2001, prepared by AMEC Earth & Environmental Limited

The permittee must implement the plan for long-term management of sludge, proposed and designed in these three reports, with the following conditions:

2.10.1 That the permittee undertake a monitoring program to include the requirements of Section 3.7;

2.10.2 That a toe drain collection system be maintained, that seepage collected from the sludge management facility is contained within the catchment

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

area of the tailings impoundment and that monitoring and analysis of collected leachate be undertaken according to the requirements of Section 3.7;

- 2.10.3 That the permittee install perimeter fencing to exclude wildlife and livestock from the area of the sludge impoundment, the toe drain and collection structures, and that the fencing be constructed to standards recommended by the Ministry's Wildlife Program; and
- 2.10.4 That the permittee install flow-measuring devices to record the volumes of sludge delivered to the storage facility and leachate flowing from the collection system to the tailings impoundment.

The characteristics of the discharge (dry basis), for information purposes only, include molybdenum at approximately 5%, by weight, iron at approximately 40%, by weight, sulphate at approximately 12%, by weight, silica at approximately 2%, by weight, and the remainder being oxygen (as oxy-hydroxide cations), minor quantities of other metals and other cations.

2.11 Dissolved Manganese Exceedances in Polishing Pond Effluent

- 2.11.1 Where it is necessary, for the protection of the integrity of the tailings impoundment structures (and, hence, public safety), to treat and discharge tailings supernatant with elevated manganese concentrations, the permittee is authorized to exceed the permitted discharge standard of Section 1.1.3, provided that the water quality requirement for manganese at the Peachland Irrigation Intake, in Section 2.1, is not exceeded at any time.
- 2.11.2 The permittee must notify the Director, in writing, of any potential exceedances of the discharge standard of Section 1.1.3 and include a plan to manage the discharge in order to comply with the requirements of Section 2.1

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

3. MONITORING AND REPORTING REQUIREMENTS

3.1 Sampling and Monitoring

The permittee must undertake the attached Sampling and Monitoring Program and the results thereof submitted to the Director. The need for increased or decreased monitoring will be based on the results submitted as well as any other data obtained by the Ministry of Environment in connection with these discharges.

Sampling is to be carried out in accordance with procedures described in the latest version of "British Columbia Field Sampling Manual for Continuous Monitoring plus the Collection of Air, Air-Emission, Water, Wastewater, Soil, Sediment and Biological Samples (permittee edition)."

A copy of the above manual may be purchased from Queen's Printer Publications Centre. A copy of the manual may also be available for inspection at Environmental Protection Program offices.

3.2 Chemical Analyses

Analyses are to be carried out in accordance with procedures described in the latest version of "British Columbia Environmental Laboratory Manual for the Analysis of Water, Wastewater, Sediment and Biological Materials, (permittee edition)", or by suitable alternative procedures as authorized by the Director.

A copy of the above manual may be purchased from Queen's Printer Publications Centre. A copy of the manual may also be available for inspection at all Environmental Protection Program offices.

3.3 Quality Assurance Plan (QAP)

Throughout all sample collection and analysis activities, the permittee must use Quality Assurance/Quality Control procedures, protocols and guidelines described in the QA/QC section of the latest edition of BC Field Sampling Manual.

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

The permittee must amend the facility-specific QAP whenever there is a modification in sample collection, sample analysis, or other procedure addressed by the QAP. A copy of the QAP must be kept on site and made available to EPD staff upon request.

3.4 **Toxicity**

The Director may impose further requirements for toxicity measurements in the future.

3.5 **Discharge Monitoring Program**

The permittee must sample the discharge to MacDonald Creek twice per week, and analyze the samples for the following parameters:

1. Dissolved molybdenum
2. Dissolved sodium
3. Dissolved sulphate
4. pH
5. Total and dissolved iron
6. Hardness
7. Conductivity
8. Dissolved manganese
9. Dissolved copper
10. Dissolved zinc
11. Dissolved solids
12. Suspended solids
13. Turbidity

3.6 **Groundwater Monitoring Program**

Once every 5 years (next sampling period in 2018), preferably in September, at piezometers numbered 86-01-1, 86-01-2, 86-02-1, 86-02-2, 86-03-1, and 86-03-2 (referenced in Appendix 01), the permittee must record the water level, sample the water, and analyze the samples for the following parameters:

1. dissolved molybdenum
2. dissolved copper
3. dissolved nitrate plus nitrite nitrogen

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

4. dissolved sodium
5. dissolved sulphate
6. dissolved manganese
7. pH
8. conductivity

3.7 **Sludge Management Facility Monitoring Program**

During periods of wastewater treatment plant operation, the permittee must record the daily volume of sludge delivered to the storage facility and the daily volume of leachate flowing from the collection system to the tailings impoundment

If any dried sludge is removed from the facility for offsite removal or alternate use, the volume of removed material and destination location will be recorded and reported in that year's annual report referred to in section 4.3.

3.8 **Surface Waters Monitoring Program (Discharge Related)**

The permittee must obtain representative samples from surface waters monitoring sites according to the schedule referenced in Appendix 02, and analyze for the following parameters:

1. dissolved molybdenum
2. dissolved copper
3. dissolved sodium
4. dissolved sulphate
5. dissolved chloride
6. pH
7. conductivity
8. total dissolved solids
9. turbidity
10. hardness
11. total and dissolved iron
12. dissolved manganese
13. total suspended solids

With the exception of Station 5 - Trepanier Cr. U/S MacDonald Cr, Station 6 -Trepanier Cr. D/S Macdonald Cr, Station 7- Trepanier Creek @ Irrigation

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

Intake and Station 8 -Trepanier Cr @ Okanagan Lake which do not require dissolved chloride, total dissolved solids and turbidity from the above parameter list.

If, in any single sample, the water quality limit for any parameter exceeds the limits of Section 2.1, the schedule for Section 3.8 must revert to daily sampling and analysis, until such time as the standard is re-attained.

3.9 **Pit Monitoring Program**

Sample the pit water at the surface, at depths of 5 meters and 10 meters, and at 10-meter depth intervals thereafter, once every ten years, and analyze for the parameters listed in Section 3.6, plus dissolved oxygen and temperature (in degrees Celsius). According to this schedule, the next pit profile is due in 2023.

3.10 **Surface Waters Monitoring Program (Non-discharge Related)**

The permittee must obtain representative samples from surface waters monitoring sites according to the schedule referenced in Appendix 03, and analyze for the following parameters:

1. dissolved molybdenum
2. dissolved copper
3. pH
4. conductivity
5. dissolved sulphate

3.11 **Flow Measurement**

Once per day, during periods of discharge, the permittee must measure the flow of effluent discharge, in litres per second.

4. **REPORTING REQUIREMENTS**

4.1 **Maintenance of Records**

Maintain records of pump rates, discharge volumes, tailings impoundment water levels, pit water levels, field measurements, chemical analyses and any other monitoring or reporting requirements of this permit, for a minimum of seven years.

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

4.2 Monthly Report

Maintain data of analyses and flow measurements required under Sections 3.5, 3.7, 3.8, and 3.11 for inspection, and submit the data, suitably tabulated, to the Director on a monthly basis in electronic format. The monthly reports must be submitted within 30 days of the end of the month in which the data was collected.

The permittee must ensure that the analytical laboratory performing chemical and biological analyses electronically upload the results directly to the Ministry's data base, once the results are finalized.

4.3 Annual Report

The permittee must compile an annual report consisting of, but not limited to, summaries of the operation of the treatment facility, the discharge quality and quantity, operation of the sludge management facility (including sludge volumes entering and effluent volumes leaving), sampling and analytical requirements, pit water elevations, analyses of attainment and trends in environmental monitoring (both source and impact), public and agency consultation undertaken and proposals for action to resolve existing and potential problems with the operations on site, environmental impacts or attainment of environmental quality objectives.

Annual reports must be submitted within 60 days of the end of the calendar year.

5. PUBLIC PARTICIPATION

The permittee must promote public participation as a means of providing an avenue or mechanism for public input and consultation for addressing public concerns regarding the discharge authorized by Permit PE-263. The permittee's promotion of such public participation must include:

- a) Supporting the formation of a public awareness committee as the need arises.
- b) Extending an invitation to First Nations to participate in the committee.
- c) Co-operating with the District of Peachland in witnessing the monitoring program of Permit PE-263, and sharing monthly results of the Peachland intake water quality.

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

6. PROVISION OF INFORMATION ACCESSIBLE ON THE INTERNET

The permittee must during periods of discharge, on a monthly basis, prepare a newsletter which illustrates in graphical form the water quality monitoring results for molybdenum, sodium, sulphate and hardness at the Peachland Irrigation District Intake on Trepanier Creek.

- a) The format of information may be revised as directed by the director;
- b) Have the information accessible and maintained on the Internet.

7. EMS

The Permittee must ensure that all data collected under this monitoring plan is uploaded into the Environmental Monitoring System (EMS database).

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

APPENDIX 01

**GROUNDWATER MONITORING SITES
(REFERENCE SECTION 3.6)**

SITE	DESCRIPTION	PIEZOMETER	AMS NO.	EMS NO.
MW1	Low Grade Stockpile Piezometer Nest	86-02-01	32	E220716
		86-02-02	33	E220717
MW2	Piezometer Nest Near MacDonald Creek	86-01-01	34	E220718
		86-01-02	35	E220719
MW3	Screening Plant Piezometer Nest	86-03-01	36	E220720
		86-03-02	37	E220721

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

APPENDIX 02

**SURFACE WATER MONITORING SITES - DISCHARGE RELATED
(REFERENCE SECTIONS 3.5 and 3.8)**

STATION	DESCRIPTION	SAMPLING FREQUENCY	AMS NO.	EMS NO.
1	Tailings Impoundment	SPRING (mid-freshet) and FALL (low flow conditions)	1	0500358
2	Lower Reclaim Pond	SPRING (mid-freshet) and FALL (low flow conditions)	2	0500361
3	D/S Lower Reclaim	SPRING (mid-freshet) and FALL (low flow conditions)	3	0500044
22	Discharge to MacDonald Creek	See Section 3.5	41	E226070
5	Trepanier Cr. U/S MacDonald Cr.	QUARTERLY, (winter quarter excluded)	5	0500362
6	Trepanier Cr. D/S MacDonald Cr.	MONTHLY, during discharge periods, then QUARTERLY (winter months excluded)	6	0500079
7	Trepanier Cr. @ Irrigation Intake	WEEKLY, during discharge periods, then QUARTERLY	7	0500352
8	Trepanier Creek @ Okanagan Lake	QUARTERLY	8	0500078
19	MacDonald Creek d/s Gravel Pit	OPTIONAL	38	E220725
20	MacDonald Creek @ Trepanier Cr.	OPTIONAL	39	E220726

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

APPENDIX 03

**SURFACE WATER MONITORING SITES - NON-DISCHARGE
RELATED
(REFERENCE SECTION 3.10)**


STATION	DESCRIPTION	SAMPLING FREQUENCY	AMS NO.	EMS NO.
9	Peachland Creek U/S Mine	EVERY SECOND YEAR	9	0500354
11	Upper Reclaim Pond (Saddle Dam)	TWICE PER YEAR	17	0500787
12	Peachland Creek Diversion U/S Peachland Lake	EVERY THREE YEARS - SPRING (mid-freshet) and FALL (low flow conditions)	12	0500355
13	Peachland Lake near Dam	EVERY THREE YEARS - SPRING (mid-freshet) and FALL (low flow conditions)	13	0500360
14	Peachland Creek @ Ok Lake	EVERY THREE YEARS - SPRING (mid-freshet) and FALL (low flow conditions)	14	0500056
15	Peachland Creek @ P.I.D. Intake	EVERY THREE YEARS - SPRING (mid-freshet) and FALL (low flow conditions)	26	0500856
16	Seepage d/s of Upper Reclaim	TWICE PER YEAR	18	0500788
21	MacDonald/Long Weir @ Confusion Point	TWICE PER YEAR	40	E220727

Date issued: February 20, 1969
Date amended: August 29, 2019
(most recent)



Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

SITE PLAN




Date issued:
Date amended:
(most recent)

February 20, 1969
August 29, 2019

Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region

LOCATION MAP



Date issued:
Date amended:
(most recent)

February 20, 1969
August 29, 2019

Carol Danyluk, P.Eng.
for Director, *Environmental Management Act*
Okanagan Region